









➔ BUSINESS SHREDDERS IDEAL 2501

OFFICE SHREDDERS - IDEAL FOR WORK GROUPS

SPS - (Safety Protection System) package: electronically controlled, transparent safety flap in the feed opening as additional safety element; EASY_SWITCH – intelligent control element indicating the operational status of the shredder with varying colour codes and back-lit symbols; automatic reverse and power cut-off (avoids paper jams); automatic stop if the shred bag is full; electronic door protection via a magnetic proximity switch; double motor protection; energy saving mode | photo cell controlled automatic start and stop | convenient 260 mm feed opening | high quality paper clip proof cutting shafts from special hardened steel | strip cut model and 4 x 40 mm cross cut model suitable for safe shredding of CDs/DVDs | 5 years guarantee on the cutting shafts | quiet but powerful 580 Watt single phase motor | dust-proof gear box housing and durable gears | high-quality wooden cabinet, mobile on castors | bag frame for disposable shred bags | 75 litres volume for the shreds

Power connection²: 230 V / 50 Hz / 1~, Dimensions (H x W x D): 720 x 500 x 377 mm, Weight: 27 kg / 27.5 kg (Cross/Cut).



Cutting size	shreds effortless
4 mm	  
4 x 40 mm	  
2 x 15 mm	 

EASY_SWITCH



Intelligent multifunction switch element with integrated optical signals for the operational status.

TRANSPARENT SAFETY FLAP



Outstanding safety features: SPS includes an electronically controlled safety flap in the feed opening.

➔ IDEAL 2501

Cutting width	4 mm
Sheet capacity ¹	21-23 18-20
Security level	2
Feed opening	260 mm
Motor capacity	580 Watt

➔ IDEAL 2501-C/C

Particle size	4 x 40 mm
Sheet capacity ¹	16-18 13-15
Security level	3
Feed opening	260 mm
Motor capacity	580 Watt

➔ IDEAL 2501-C/C

Particle size	2 x 15 mm
Sheet capacity ¹	10-12 8-10
Security level	4
Feed opening	260 mm
Motor capacity	580 Watt

¹ A4 paper, 70 g/m² | 80 g/m²

² other voltages available



I.T.E. Listed 802 D