→ BUSINESS SHREDDERS **IDEAL 3103**

OFFICE SHREDDERS WITH 310 MM (12") FEED OPENING FOR A3

SPS - (Safety Protection System) package: electronically controlled, transparent safety flap in the feed opening as additional safety element; EASY_SWITCH - intelligent control element indicating the operational status of the shredder with varying colour codes and back-lit symbols; automatic reverse and power cut-off (avoids paper jams); automatic stop if the shred bag is full; electronic door protection via a magnetic proximity switch; double motor protection; energy saving mode | photo cell controlled automatic start and stop convenient 310 mm feed opening high quality paper clip proof cutting shafts from special hardened steel strip cut model and 4 x 40 mm cross cut model suitable for safe shredding of CDs/DVDs 5 years guarantee on the cutting shafts | quiet but powerful 640 Watt single phase motor for continuous operation | dust-proof gear box housing and durable gears | high-quality wooden cabinet, mobile on castors | plastic bag suspension with pull-out mechanism on wheels for easy removal of the full bag | 140 litres volume for the shreds

Power connection²: 230 V / 50 Hz / $1\sim$, Dimensions (H x W x D): 930 x 538 x 470 mm, Weight: 49.5 kg / 50 kg (Cross/Cut).



PLASTIC BAG SUSPENSION



The plastic bag suspension on wheels allows an easy and

convenient removal of the full shred bag.

QUALITY METAL HINGES



All purchased parts are tested

for quality and reliability, like

these high-quality metal hinges

for the cabinet door.

→ IDEAL 3103

Cutting wiath	4 111111
Sheet capacity ¹	24-26 20-22
Security level	2
Feed opening	310 mm
Motor capacity	640 Watt

→ IDEAL 3103-C/C

Particle size	4 x 40 mm
Sheet capacity ¹	18-22 15-19
Security level	3
Feed opening	310 mm
Motor capacity	640 Watt

→ IDEAL 3103-C/C

Particle size	2 x 15 mm
Sheet capacity ¹	10-12 8-10
Security level	4
Feed opening	310 mm
Motor capacity	640 Watt
riului capacity	U4U VVall

1 A4 paper, 70 g/m² | 80 g/m² ² other voltages available





4 x 40 mm

2 x 15 mm