↦ BUSINESS SHREDDER **IDEAL 4005**

INNOVATIVE HIGH CAPACITY OFFICE SHREDDERS – HIGH PERFORMANCE AND LARGE VOLUME

SPS - (Safety Protection System) package: electronically controlled, transparent safety flap in the feed opening as additional safety element; EASY_SWITCH – intelligent control element indicating the operational status of the shredder with varying colour codes and back-lit symbols; automatic reverse and power cut-off (avoids paper jams); automatic stop if the shred bag is full; electronic door protection via a magnetic proximity switch; double motor protection; energy saving mode | photo cell controlled automatic start and stop | ECC - Electronic Capacity Control – indication of the used sheet capacity during shredding process | automatic oil injection on the cutting shafts during shredding operation for constantly high shred performance | convenient 405 mm feed opening | high quality paper clip proof[2] cutting shafts from special hardened steel | models IDEAL 4005 and IDEAL 4005-C/C suitable for safe shredding of CDs/DVDs | 5 years guarantee[2] on the cutting shafts | quiet but powerful 1600 Watt single phase motor for continuous operation | sturdy chain drive and dust-proof gear box housing | high-quality wooden cabinet, mobile on castors | plastic bag suspension with pull-out mechanism on wheels for easy removal of the full bag (models M/C and SM/C with shred container) | approx. 225 litres volume for the shreds

Power connection[3]: 230 V / 50 Hz / 1~, Dimensions (H x W x D): 1010 x 640 x 590 mm, Weight: 115 kg

SAFETY PROTECTION SYSTEM SPS MADE BY IDEAL

IDEAL TOP GUARANTEE 5 YEARS ON THE SHREDDING SHAFTS

ENERGY SAVING MODE ESM IDEAL FOR OUR ENVIRONMENT!

Cutting size	shreds effortless
6 mm	
4 x 40 mm	
2 x 15 mm	

GS

CE

c UL us I.T.E. Listed 802 D

ECC CONTROL

ECC – Electronic Capacity Control: for continuous feeding without creating paper jams the used sheet capacity is indicated during the shredding process.

↦ IDEAL 4005	
Shred width	6 mm
Sheet capacity[1]	50-55 | 42-47
Security level	2
Feed opening	405 mm
Motor capacity	1600 Watt
↦ IDEAL 4005-C/C	
Particle size	4 x 40 mm
Sheet capacity[1]	40-45 | 34-39
Security level	3
Feed opening	405 mm
Motor capacity	1600 Watt
↦ IDEAL 4005-C/C	
Particle size	2 x 15 mm
Sheet capacity[1]	25-30 | 21-26
Security level	4
Feed opening	405 mm
Motor capacity	1600 Watt
↦ IDEAL 4005-M/C	
Particle size	0.8 x 12 mm
Sheet capacity[1]	15-17 | 13-15
Security level	5
Feed opening	405 mm
Motor capacity	1600 Watt
↦ IDEAL 4005-SM/C	
Particle size	0.8 x 5 mm
Sheet capacity[1]	10-11 | 8-9
Security level	"Level 6"
Feed opening	405 mm
Motor capacity	1600 Watt

[1] A4 paper, 70 g/m² | 80 g/m²
[2] 4005-M/C 0.8 x 12 mm and 4005-SM/C 0,8 x 5 mm: Paper clips and staples have to be removed before shredding. Guarantee 1 year.
[3] other voltages available

IDEAL