



# EXCELAM II-355Q/655Q

Business Roll Laminator  
Hot Roller Type Roll Laminator



- Installed Safety Device (Slide Latch)
- Hot Roller Technology
- Speed and Temperature Control
- Hot Lamination
- Mounting up to 5mm thick Foamboard
- 8-bit Microprocessor Controlled Preset Functions
- Accurate Temperature Measurement with use of Infrared Infrared Sensor
- Transparency Roller Cover is Easily Detached with use of Magnets

EXCLAM II-355Q/655Q

[www.gmp.com](http://www.gmp.com)



This cover is laminated with GMP NYLONEX by using GMP PIONEER II-8000BC. NYLONEX is curling and scratch-free, high glossy super-bond-film.

 **GMP CO., LTD.**



# EXCELAM II-355Q/655Q

## Roll Laminator

Superb laminating results with a wide range of Heat Seal laminating films from 32mic to 250mic.

Features include variable speed, temperature and pressure control, LCD readout, Pre-set functions, mounting capability.

Improvement in temperature sensing by measuring directly off the hot roller surface with use of Non-Contact Infrared Optic sensor circuit.

Accurate and stable temperature regulation allows the machine to perform lamination in more professional fashion.

Improved user friendly features include easy detachment of plexi roller cover and employment of slide latch for loading/unloading front tray upon changing bottom laminating roll.

EXCELAM II series is the perfect machine to produce a wide range of service in a copy shop environment or as an in-house office laminator.

Ideal for laminating posters, inkjet prints, leaflets and maps with superb results, and for truly professional mounting onto Lamifoam (Foamboard) up to 5mm thickness.



## Standard Features

- Pre-set functions include hot and cold settings, pre-heat, temperature measurement, and reverse with over-ride for full speed and temperature control
- Tension Control on Film Mandrel
- Speed Setting from 0~1.5 meters/minute
- Paper Guide on Feed Table
- MAX 5mm Thickness for FOAMBOARD® Mounting
- Variable Pressure Control

## Specifications

Model Name	EXCELAMII-355Q	EXCELAMII-655Q
Laminating Speed	1.5m/min	1.5m/min
Laminating Width	355mm	655mm
Laminating Films	25mic~500mic	25mic~500mic
Thickness of substrate(Paper)	80g/㎡~350g/㎡	80g/㎡~350g/㎡
Thickness Mount	5mm	5mm
Power Requirements	220~240V, 50/60Hz	220~240V, 50/60Hz
Power Consumption	1400W, 6.0A	1700W, 7.0A
Warm Up Time	10 minutes	10 minutes
Heating System	Hot Roller Internal Infrared Heater	Hot Roller Internal Infrared Heater
Operating Temperature	150℃ Max.	150℃ Max.
Speed Control	Key Pad	Key Pad
Temperature Control	Key Pad	Key Pad
Pressure Adjustment	Manual(6step)	Manual(6step)
Film Core	14-25WH	14-25WH
Cooling System	AC Fan	Blower
Dimensions(WxLxH)	585 x 450 x 285mm	885 x 450 x 285mm
Type of Main Motor	DC W-Geard Motor /36V70	DC W-Geard Motor /36V70
Stand	N/A	Option

GMP reserves the right to after change specifications without prior notice.